

INOXIHP
ABOUT USING WATER



PM 260

Reciprocating Horizontal
Triplex Plunger Pumps



PM 260



General features

- Compact dimension
- Forced lubrication system
- Easy maintenance
- Low maintenance costs
- Internal reduction gear
- Self-adjusting seal packing
- Available with carbon steel or stainless steel hydraulic head
- 100% aluminium free

Accessories


- Valve lifter controlled by means of pneumatic solenoid
- Unloading valve
- Over-pressure valve
- HP check valve
- Suction and/or delivery gauge
- Low and high pressure switches
- Manifold groups for suction/delivery
- ATEX Group I Category M2 Certification

Applications

- Emulsion Hydraulic power to drive Longwall systems
- Dust suppression systems on Roof Supports & Coal Shearers


Identification code

see tables on the next page >>>



Dimensions

Dimensions are referred to hydraulic head T35
Weight: kg 715



Mining Skid

Inoxihp supplies complete skids for underground coal mining (Longwall) for applications such as tunnel roof support, rotating blade cooling (shearer) and dust suppression.

Highly reliable products, also available in ATEX version.



INOXIHP S.r.l.
IT - 20834 Nova Milanese (MB) - Via Garibaldi, 89
Tel: +39 0362 190111 - E-mail: inoxihp@inoxihp.com - inoxihp.com

INOXIHP
ABOUT USING WATER